

# SEM MAT ABSOLUT

INTERIOR



**High-quality water-based alkyd resin matt paint.**

#### SUITABLE SUBSTRATES

All interior printed substrates, walls and ceilings: plasterboard, concrete, clean and cohesive old paintwork and coated substrates, cement coatings in good condition.

#### INSTRUCTIONS FOR USE

##### PREPARATION OF SUBSTRATES

Substrates must be prepared according to the rules of DTU 59.1.

##### TOOLS

Brush, roller.

##### TOOLS CLEANING

With water.

##### YIELD

From 9 to 10 m<sup>2</sup> per liter for the first coat; from 11 to 12 m<sup>2</sup> per liter for the second coat.

##### DRYING (AT 23°C – 50% RH)

Drying time: 2 hours.

Dry-to-recoat time: 6 hours

##### PRECAUTIONS FOR USE

- Do not apply at a temperature lower than +8°C relative humidity higher than 70%.
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

##### TECHNICAL INFORMATION

##### PACKAGING

Plastic buckets of 15 liters.

##### STORAGE

18 months in unopened packaging. Store away from frost.

##### SPECULAR GLOSS

1.8 % from an angle of 85°.

##### WET ABRASION RESISTANCE

Standard NF EN 1300: class 1.

##### DRY EXTRACT (BY WEIGHT)

52 %

##### DENSITY

1.43 (standard EUR PL 004).

## ADVANTAGES

- High covering power.
- Deep matt finish.
- Neat finish, no marks.

### Réglementation en vigueur :

Norme AFNOR T 36005  
FAMILLE I – CLASSE 7b2.

### Sécurité :

Produit en phase aqueuse, non soumis à l'étiquetage.

### Emissions dans l'air intérieur (selon ISO 16000) :

Ce produit contient moins de 1 g./L de COV

