

SEMMat PREMIUM

INTERIOR



**Silane-acrylic resin-based matt interior paint.
Superior quality for a neat finish.**

SUITABLE SUBSTRATES

All primed interior substrates, walls and ceilings: plaster, wood, old paintwork and sealants in good condition.

INSTRUCTIONS FOR USE

PREPARATION OF SUBSTRATES

Substrates must be prepared according to the rules of DTU 59.1.

TOOLS

Brush, roller and airless spray gun (519 nozzle).

TOOLS CLEANING

With water.

YIELD

9 to 10 m² per liter.

DRY (AT 23°C – 50% RH)

Drying time : 2 hours.

Dry-to-recoat time : 6 hours

PRECAUTIONS FOR USE

- Do not apply at a temperature lower than +8°C relative humidity higher than 70%.
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

TECHNICAL INFORMATION

PACKAGING

Plastic buckets of 15 liters.

STORAGE

18 months in unopened packaging. Store away from frost.

SPECULAR GLOSS:

2% from an angle of 85°.

WET ABRASION RESISTANCE

Standard NF EN 13300: class 1
(loss of film < 5µm and after 200 cycles).

DRY EXTRACT (BY WEIGHT)

55 %

DENSITY

1.50 (standard EUR PL 004).

ADVANTAGES

- Deep matt finish.
- Neat finish, no marks.
- Washable.

Regulations in force :

Standard AFNOR T 36005
FAMILY I – CLASS 7b2.

Safety :

Aqueous phase product,
not subject to labelling.

Emissions in indoor air (according to ISO 16000) :

This product contains less
than 1g/l of VOCs.

